

## تقاضای خرید شرکت های چکی از ایران

Another material definition	Company rating	Diameter	Tensile strength		Elongation A <sub>500</sub>	Resistance		Fiber conductivity
			Tensile strength at break	Per cent		Static resistance	Dynamic resistance	
Dati ročnice materiálu	Průmyslová značka	Průměr (mm)	σ <sub>b</sub> (N/mm <sup>2</sup> )	σ <sub>0.2</sub> (N/mm <sup>2</sup> )	σ <sub>0.2</sub> (%)	σ <sub>0.2</sub> (N/cm <sup>2</sup> )	σ <sub>0.2</sub> (N/cm <sup>2</sup> )	σ <sub>0.2</sub> (N/cm <sup>2</sup> )
EN AW-1070 O	Al 7.0	1.6	0.4	60	75*	36	2.725	(F3.3)
EN AW-1070 O	Al 8.0	0.5	0.5	60	75*	36	2.725	(F3.3)
EN AW-1070 H11	Al 8.0	0.5	0.5	60	95	18	2.765	(F1.9)
EN AW-1070 O	Al 12.0	12	0.6	60	75*	36	2.725	(F3.3)
EN AW-1070 H11	Al 12	12	0.6	60	95	18	2.765	(F1.9)
EN AW-1070 H11	Al 15	15	0.7	60	95	18	2.765	(F1.9)
EN AW-1070 H11	Al 18	18	0.8	60	95	18	2.765	(F1.9)
EN AW-1070 H11	Al 22	22	1.0	60	95	18	2.765	(F1.9)
EN AW-1070 H11	Al 25	25	1.3	60	95	18	2.765	(F1.9)

